

# Permanent Pothole Repair

## Cold Lay Asphalt Concrete

**ULTRA**  
**CRETE**

Cold Lay Asphalt Concretes



Ideal for the repair of potholes in roads, driveways and car parks.

- **Easy work formula**
- **Easier to compact**
- **HAPAS Approved since 2011**
- **Instantly trafficable**
- **No waste, resealable buckets**
- **Easy to apply**
- **Depth: 10-100mm**
- **For planned and reactive repairs**

### Applications

UltraCrete Permanent Pothole Repair is a suitable solution for roads, pavements, driveways and car parks. The product can be trafficked instantly in wet, freezing and hot conditions and at the same time is compatible with the existing road surface. Permanent Pothole Repair can be applied at depths up to 100mm. (Greater depths can be achieved by applying the layer-on-layer method).

### Technical

UltraCrete Permanent Pothole Repair includes fully graded, high PSV interlocking aggregate and specially formulated bitumen and is supplied in recyclable 25kg containers.

### Application

Pothole repairs can be achieved at any depth.

1. Ensure pothole is free of debris and standing water.
2. Apply UltraCrete SCJ spray sealant to pothole edges.
3. Apply the product slightly proud of the pothole.
4. Compact with a hand tamper, or suitable mechanical alternative.

### Storage

Store in a cool and well-ventilated place

### Shelf life

Shelf life in correct conditions for sealed goods is:

Bucket: 6 months – Delivered on shrinkwrapped pallets

### Handling guidelines

UltraCrete Permanent Pothole Repair is manufactured and delivered within as short a time as possible to ensure fresh easy to lay material is supplied.

### Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from [instarmac.co.uk](http://instarmac.co.uk)

### Quality assurance

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001. Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.



Technical data

PSV	60
Colour	black
Coverage	Approx 1m <sup>2</sup> at 12-15mm compacted, depending on the surface regularity of the reinstatements
Unit/packaging	25kg bucket (52 units per pallet)

Contact Us

Instarmac® Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 254400 Fax: +44 (0) 1827 285386

Email: [email@instarmac.co.uk](mailto:email@instarmac.co.uk) Order: [orders@instarmac.co.uk](mailto:orders@instarmac.co.uk) Website: [instarmac.co.uk](http://instarmac.co.uk)

Vers10.1.19Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at [www.ultracrete.co.uk](http://www.ultracrete.co.uk)