

INSTARMAC

SAFETY DATA SHEET **UltraTileFix ProGrout Flexible Silver Grey**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UltraTileFix ProGrout Flexible Silver Grey

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc
Danny Morson Way
Birch Coppice Business Park
Dordon, Tamworth
Staffordshire. B78 1SE
United Kingdom
Tel: +44 (0) 1827 872244
Fax: +44 (0) 1827 874466
email@instarmac.co.uk www.instarmac.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1827 254433 +44 (0)7971 217 347 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT RE 1 - H372
Environmental hazards Aquatic Chronic 3 - H412

Human health See Section 11 for additional information on health hazards.

Environmental The product is not expected to be hazardous to the environment.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

UltraTileFix ProGrout Flexible Silver Grey

Precautionary statements

P260 Do not breathe dust.
 P261 Avoid breathing dust.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/ doctor.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P314 Get medical advice/ attention if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains CRISTOBALITE FLOUR, WHITE OPC

Supplementary precautionary statements

P260 Do not breathe vapour/ spray.
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P314 Get medical advice/ attention if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Classification according to EC 1272/2008 (CLP)

3.2. Mixtures

CRISTOBALITE FLOUR	30-60%
CAS number: 14464-46-1	EC number: 238-455-4
Classification	
STOT RE 1 - H372	

UltraTileFix ProGrout Flexible Silver Grey

WHITE OPC	30-60%
CAS number: —	
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	
CALCIUM ALUMINATE CEMENT	5-10%
CAS number: —	
Classification Not Classified	
VINYL ACETATE COPOLYMER	1-5%
CAS number: —	EC number: 925-954-3
Classification Not Classified	
BLACK PIGMENT	<1%
CAS number: 1133-86-4	
Classification Not Classified	
POLYVINYL ALCOHOL AND SILANE	<1%
CAS number: —	
Classification Not Classified	
2-OCTYL-2H-ISOTHIAZOL-3-ONE	<1%
CAS number: 26530-20-1	EC number: 247-761-7
M factor (Acute) = 100	M factor (Chronic) = 100
Classification Acute Tox. 4 - H302 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

UltraTileFix ProGrout Flexible Silver Grey

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person.
Skin contact	Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known. No unusual fire or explosion hazards noted.
Hazardous combustion products	Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment.
----------------------------------	-----------------------------------

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	GENERAL. For waste disposal, see Section 13.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13. See Section 11 for additional information on health hazards.
------------------------------------	--

UltraTileFix ProGrout Flexible Silver Grey

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at moderate temperatures in dry, well ventilated area.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

CRISTOBALITE FLOUR

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³ resp.dust

WHITE OPC

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³

CALCIUM ALUMINATE CEMENT

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

VINYL ACETATE COPOLYMER

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³

BLACK PIGMENT

Long-term exposure limit (8-hour TWA): WEL 3.5 mg/m³

POLYVINYL ALCOHOL AND SILANE

Long-term exposure limit (8-hour TWA): 4 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Not relevant.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

UltraTileFix ProGrout Flexible Silver Grey

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Dusty powder.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

General information No specific health hazards known.

Inhalation No specific health hazards known.

Ingestion May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea.

Skin contact Irritating to skin.

Eye contact Irritating to eyes.

Acute and chronic health hazards This product may cause skin and eye irritation.

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

UltraTileFix ProGrout Flexible Silver Grey

Toxicity No information available

12.2. Persistence and degradability

Persistence and degradability No information available There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is non-volatile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

UltraTileFix ProGrout Flexible Silver Grey

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

Guidance Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

Issued by HS&E Manager.

Revision date 31/01/2018

SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.