



class	L551.N172		
code	(4-)	P	(G4)


# premadhesive

for fixing cove and cornice systems

working time



Suitable for fixing all gypsum and fibrous mouldings including cove and cornice systems.



- Just mix with water for easy installation
- High grab and strong adhesion
- Dries white for easy over painting
- Excellent coverage, up to 167 linear metres

available in

**12.5kg**  
bag

# premadhesive

for fixing cove and cornice systems

### Surface Preparation

It is imperative that all surfaces are clean, sound and dry prior to application. All decorative wall papers should be removed to uncover the original surface. Painted surfaces should have all loose and flaky materials, including distempered finishes removed. Once this is thoroughly completed, all working areas of the wall and ceiling should be keyed by scratching the surface and then sealed using UltraFloor Prime IT Multi-surface Primer, diluted 5 parts water to 1 part primer. Apply one coat and allow to dry before proceeding.

### Recommendations

Fibrous mouldings can vary considerably in size and weight, and therefore it is recommended that all types are screw fixed in addition to using Wondertex prem adhesive.

During colder weather conditions on unheated sites, it is recommended to mix Wondertex prem adhesive with warm water to ensure ingredients dissolve fully.

Freshly plastered surfaces MUST be completely dry before application.

As background surfaces can vary considerably, it is strongly recommended that trial compatibility and stability tests are carried out in all instances.

### Mixing

Always use clean water, bucket and tools. The suggested mix ratio is 1 part water to 2 parts powder. Alternatively 5.8 litres of water per 12.5kg bag. Add Wondertex prem adhesive to the water and mix thoroughly until a smooth lump free consistency is achieved. Allow mixed material to stand for 5 minutes then mix again before use. If required add more powder (or water) to achieve the required consistency.

### Application

#### Coving

Apply Wondertex prem adhesive 3-5mm thick along the two edges of the coving which adhere to the wall and ceiling. Move coving into required position and press firmly into place. Screw fix in position if required. Remove excess material with a damp sponge.

#### Fibrous Mouldings

Apply Wondertex prem adhesive 3-5mm thick on all surfaces that will come into contact with the wall and ceiling. Move fibrous moulding into required position and press firmly into place. Screw fix in position if required. Remove excess material with a damp sponge.

### Coverage

Covers up to 167 linear metres of coving.

### Storage

The product must be stored in temperatures above 5°C and not exceeding 30°C, in a dry place.

### Shelf Life

6 months in original unopened bags if stored in the conditions stated.

### Notes

Wondertex prem adhesive has a working time of 60-90 minutes. Only mix sufficient material that can be used in this time.

Do not use in temperatures less than 3°C. Temperatures must also remain above 3°C during drying time.

Clean any accidental splashes from floors etc. with warm water before drying.

### Health & Safety

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full Material Safety Data Sheet relating to this product is available from instarmac.co.uk.

### Quality Assurance

All products are manufactured in a plant whose quality management system is certified/registered as being in conformity with BS EN ISO 9001, ISO 14001 and OHSAS 18001. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our projects are used. All products are sold subject to our conditions of sales, copies of which may be obtained upon request.

	premadhesive fill & finish	premadhesive texture	premadhesive adhesive	premadhesive finish	premadhesive filler
sizes	7.5kg & 15kg	25kg	12.5kg	25kg	12.5kg
bonding	•		•		
repairing	•			•	•
jointing	•			•	•
filling	•				•
smoothing	•	•		•	
snagging	•			•	
texturing		•			
working time	60mins	60-90mins	60-90mins	180mins	60-90mins
apply 2nd coat	2-4hours	n/a	n/a	3-5hours	n/a