

UltraFloor helps showcase a legendary brand



Aiken Flooring Contracts have completed subfloor preparation using UltraFloor materials on a Harley Davidson showroom project in Gateshead.

CONTRACTOR: AIKEN FLOORING CONTRACTS

MATERIALS USED: DPM IT, LEVEL IT TWO, PRIME IT MSP

The project was secured by CFA member, Aiken Flooring Contracts who worked to a tight deadline and finished the showroom floor in only 4 weeks. The work included floor prep, priming, damp proofing, bulking out and levelling prior to floor covering application. The UltraFloor range of materials were chosen due to their reliable performance and helped to secure a successful and cost-effective project.

UltraFloor Prime IT Multi-surface Primer was used prior to the application of the damp proof membrane and leveller. This popular primer is suitable for porous and non-porous substrates, enhancing adhesion and reducing pinholing for a bond-proof installation.

Rapid curing primer membrane, DPM IT is designed



to provide protection against subfloor moisture. Boasting a 98%RH floor moisture tolerance the two-part epoxy resin system cures in 5 hours.

High flow, two-component smoothing underlayment Level IT Two can be applied at depths between 2 and 12mm. For deeper sections up to a maximum of 30mm, as required in the showroom, a graded aggregate filler can be used to bulk out prior to levelling. Low odour and protein free, Level IT Two can be overlaid after 12 hours with bonded floor coverings.